	PI	ERMIT TO	O CONSTR	UCT 1	Date: _			
APPLICANT			FIELD ENT	LJ	]	Receipt	#	
BILLING ADDRE	ass		(	City/ST/Zip				
In accordance installation, widening Construction of drive of Costs). After apprenticular construction of costs of Costs.	ng, or moving or reways and fiel	of driveways d entrances	and field entra may be by app	ances must be a dicant or Coun	approve ty Force	d by the s (at an	Engineer's Office. established schedule	
Township				N	7	7 Mark		
							wark Location in	
Sec. #			w L		_ E		box.	
Street # or Avenue	#					F1	ag location on	
Desired width	ft					sit	•	
Drainage pipe nece	essary?			S	_			
New	Extension _	<del></del>	Other _					
Constructed by		Cons	t. Date Reque	sted				
Materials:								
T CD'	CMP Pipe	Quantity	Diameter	Length	Total	Cost		
Type of Pipe								
New	CMP Pipe							
(Should be New)	Bands							
Used	Labor							
			Delivery ch	arge on pipe	\$	50.00		
			TO	TAL COST				
Mandatory Pipe checkout Rece	ipt No:		Notify t	he Office (Inv	entory)	?		
		In	ventory Rem	oved by Offic	e			
Signature of Applic	eant							
Reviewed by			Date					
(Forem	ian)							

## SCHEDULE OF COSTS

# <u>PAYMENT OF ENTRANCES</u>: Payment will be made <u>before</u> construction begins or when pipe is picked up.

Palo Alto County will stock the material and furnish the labor and equipment to construct the driveway or field entrance. The person requesting the driveway or field entrance will pay for the material at the following rate:

\$400.00 Plus Cost of Pipe 24' Wide Top Single

\$400.00 Without Culvert Pipe 24' Wide Top Single

\$150.00 Per Side up to 10' for Widening (Plus Cost of Pipe)

# § 50.00 Delivery Charge – always charge for this service.

15" Metal pipe \$12.75 per ft, connecting band \$25.50 each.

18" Metal pipe \$14.50 per ft, connecting band \$29.00 each.

24" Metal pipe \$19.25 per ft, connecting band \$38.50 each.

### MOVING OF FIELD ENTRANCES AND DRIVEWAYS: Will be done at same cost as new driveway.

Driveways and field entrances shall not be placed by the landowners or tenant on any road without the consent of the Engineer, even though the owner or tenant does the work. Driveways placed without such consent shall be subject to removal at owner's expense. Driveways requiring pipe shall have the minimum diameter of 15" and shall be 16 gauge corrugated metal.

#### **CONSTRUCTION STANDARDS**

New construction or expansion of existing drives will conform to county standards.

Top width, Single – 24'

Top width, Double (shared) – 34'


Side width, Gravel road -3' width for every 1' ditch depth

Side width, Paved road (with pipe) -6' width for every 1' ditch depth

Side width, Paved road (without pipe) – 8' width for every 1' ditch depth

Location restrictions:

- Placed no closer than 150' from near edge of intersecting road.
- <u>Field Entrances on gravel roads</u> may be placed no closer than 60' from nearest edge of intersecting roads. However, the goal is to have at least 150' separation from the edge of the intersecting road for better snow removal and safety.



<sup>\*</sup> Pipes longer than 60' must be a minimum of 18" to minimize plugging with debris.